

Touch-protected BNC Connectors and BNC Panel-mount Sockets


XBS-58 XBK-58

Touch-protected BNC male and female connectors for production of touch-protected


BNC leads (RG58). Shield is nickel-plated, the contact pins and sockets of the inner

conductor are in gold-plated brass.

XBS-58







XBK-58



Order No.	Type	Assembly instructions		*Colours
67.9760-*	XBS-58	MAH 529	Au Ni	21 22 23 28
67.9762-*	XBK-58	MAH 540	Au Ni	21 22 23 28

Technical Data

Type	XBS-58	XBK-58
Rated voltage / current	1000 V, CAT II (600 V, CAT III) / 1 A	600 V, CAT II (300 V, CAT III) / 1 A
Frequency range	0 ... 3000 MHz	0 ... 3000 MHz
VSWR (frequency-dependent) Typical values!	f = 2000 MHz: < 1.2 	f = 2000 MHz: < 1.2 
Insertion loss (frequency-dependent) Typical values!	f = 2000 MHz: < 0.2 dB 	f = 2000 MHz: < 0.4 dB 
Connectable coaxial lead: Type / outer diameter	RG58 / ~ Ø 5 mm	RG58 / ~ Ø 5 mm
Temperature range	+5°C ... +40°C	+5°C ... +40°C



Assembly instructions MAH 529, MAH 540

www.staubli.com/electrical